

FORMATIONS

Through Body
Porcelain Wall &
Floor Tile

floridatile

FORMATIONS

BY **floridat**ile

Formations combines modern style with an impeccable eye for detail. The color palette lends itself well to a transitional or contemporary decorating style. Formations includes a complete selection of Mosaics, Listellos and Inserts. Formations is so durable and can be used for both residential and commercial settings. See Formations at a dealer or distributor near you or visit us at www.floridatile.com.

through body porcelain floor & wall tile

6x6 • 12x12 • 18x18 • 12x24



25204 Quartz



25205 Flint



25213 Gravel



25282 Boulder



25296 Dark Pebble



25204 Quartz



25205 Flint



25213 Gravel



25282 Boulder
(12x24) not available



25296 Dark Pebble

12x24



25204 Quartz



25205 Flint



25213 Gravel




25296 Dark Pebble

mosaics



25204/M12 Quartz




25205/M12 Flint



25213/M12 Gravel



25282/M12 Boulder



25296/M12 Dark Pebble



25204/M2x4 Quartz



25205/M2x4 Flint



25213/M2x4 Gravel



25282/M2x4 Boulder



25296/M2x4 Dark Pebble

Shown on Front: 25213 12x12 Gravel, 2522B/L1.25x12 Geyser Listello Cold



Shown: 25296/M2x4 Dark Pebble, 25296 12x12 Dark Pebble

listellos • inserts • cove base • cove base corners



2521B/L1.25x12
Geyser Listello Hot



2522B/L1.25x12
Geyser Listello Cold



2521B/16x6
Geyser Insert Hot



2522B/16x6
Geyser Insert Cold



2520A/L2x12
Lava Listello



25204 P36C9 & PB3169
Quartz



25205 P36C9 & PB3169
Flint



25213 P36C9 & PB3169
Gravel



25282 P36C9 & PB3169
Boulder



25296 P36C9 & PB3169
Dark Pebble



Shown: 25205 18x18 Flint

FORMATIONS

BY *floridatile*

Typical Uses

Formations through body porcelain floor and wall tile is appropriate for all residential and commercial, wall, countertop and backsplash applications, all residential and most commercial floor applications.

Made in the USA: With the exception of select trim and decorative pieces, this product line is Made in the USA of 40% pre-consumer recycled content, is GREENGUARD® and Porcelain Tile Certified, and meets the new DCOF AcuTest requirements to be installed in wet areas.

Notice: Not all flooring products are suitable for wet areas, specialized applications or commercial use. Please refer to the American National Standard Specifications for Ceramic tile (ANSI A137.1) for ceramic, stone and glass installation for specific usage and installation information.

Properties (Floor)	ASTM	ANSI	Results ¹
DCOF AcuTest ²	A137.1	≥0.42	Pass
Surface Scratch Hardness	Mohs	N/A	7 Mohs
Deep Abrasion ³	C-1243	N/A	P1
Break Strength	C-648	250 lbs.	450 lbs.
Water Absorption	C-373	≤0.5%	≤0.5%
Thickness	10mm (12x24), 9.5mm (all other sizes)		

¹These values vary from lot to lot.






²ANSI A137.1-2012 standard, ceramic tiles selected for level interior spaces expected to be walked upon when wet must have a minimum wet DCOF AcuTest value of 0.42.

³P1 is the highest durability rating an unglazed tile can achieve and should be suitable for the most demanding applications.

Nominal Size ¹	Metric (cm)	Pcs./Sq Ft ²
6" x 6"	15x15	4
12" x 12"	30x30	1
18" x 18"	45x45	.44
12" x 24"	30x60	.5


¹These values may vary from lot to lot.

²These values are based on actual sizes including the grout joint.

Trim	Shape	SKU	Nominal Size	Metric (cm)
Bullnose		P43C9	3"x12"	7.5x30
Cove Base		P36C9	6"x12"	15x30
Cove Outside Corner		PB3169	6"x1"	15x2.5
Bullnose		S4669	6"x6"	15x15
Bullnose Outside Corner		SN4669	6"x6"	15x15

Color Variations

Color reproductions in this printed piece may vary from actual tile colors. Final selection should be made from actual tile samples.



V2 = Slight Variation

Clearly distinguishable differences in texture and/or pattern with similar colors.



Recycled Content

